



POLIMASTER[®]
Radiation Detection Technologies



X-RAY AND GAMMA RADIATION PERSONAL DOSIMETER

PM1630

X-ray and Gamma Radiation Personal Dosimeter PM1630 is a miniature electronic dosimeter capable of solving a wide range of personal dose monitoring tasks, including:

- **measurement of personal dose equivalent (DE) and personal dose equivalent rate (DER)** of X-ray (continuous and pulsed) and gamma radiation
- **wireless on-line data transfer and off-line transfer of instrument history events** to radiation monitoring system database of different institutions.

The **real time data transfer** capability allows to use PM1630 as a mean of control and indication of DER and DE during endovascular surgical procedures and to maintain a database and perform control of personnel exposure for the period of stay in an operating room using **Automated Personal Dosimetry System PM531**.

PM1630 dosimeters can be also integrated into **Automated Personal Dosimetry System PM530** for maintaining the instrument history database and monitoring personnel exposure.

Moreover, PM1630 is equipped with Bluetooth interface for integration with **Polismart**[®] application which enables **on-line indication** of the instrument data on a smartphone or tablet computer.

Features

- Small dimensions and light weight
- Single control button
- Digital indication, sound and LED alarms
- Three clips for different wearing options
- Resistance to cleaning and disinfection agents
- Wireless charging
- Data transfer via Bluetooth
- Function of automatic countdown and display in the Polismart[®] app of safe stay near radiation hazards

Application

- Medical personnel:
 - X-ray diagnostics
 - Interventional radiology
 - Radiation diagnostics and therapy
- Operators at radioisotope laboratories
- Medical physicists
- Customs and security officers working with X-ray inspection equipment
- Other professionals who work under the risk of X-ray and gamma radiation exposure



X-RAY AND GAMMA RADIATION PERSONAL DOSIMETER PM1630

Preliminary SPECIFICATIONS

- **Dose equivalent (DE) measurement range:**
1.0 μ Sv - 10.0 Sv
- **DE measurement accuracy:** $\pm 15\%$
- **Dose equivalent rate (DER) measurement range:**
0.1 μ Sv/h - 1.0 Sv/h
- **DER measurement accuracy:** $\pm 15\%$
- **Energy range:** 15 keV - 1.5 MeV
- **Energy response relative to 0.662 MeV:**
- 29% ... +45%
- **Minimum pulse duration of X-ray and gamma radiation:** 2 ms
- **Thresholds:** 2 independent thresholds for both DE and DER
- **Alarm type:** visual and audible
- **Communication with digital devices:** Bluetooth
- **Automatic data logging:** 6000 data points
- **Possible wearing variants :**
 - in breast pocket (front clip)
 - on breast pocket (rear clip)
 - on any clothes item (with clip type "crocodile")
 - on the wrist (silicone band)
- **The color of PM1630 case:** for orders over 50 pcs, the color of the dosimeter case can be selected by the customer.
- **Power supply:** rechargeable battery (wireless charger provided)
- **Battery lifetime in run mode:**
 - ≥ 2 months with Bluetooth disabled and average dose rate up to 0.3 μ Sv/h
 - ≥ 10 days Bluetooth enabled and average dose rate up to 0.3 μ Sv/h
 - ≥ 8 h with Bluetooth enabled and average dose rate up to 1.0 Sv/h
- **Operating conditions:**
 - temperature: from -10 °C up to +50 °C
 - humidity: up to 98 % at +35 °C
 - atmospheric pressure: from 84 up to 106.7 kPa
- **Ingress protection:** IP67
- **Resistance to disinfection:** yes
- **Drop test:** 1.5 m onto concrete surface
- **Dimensions:** 63 x 50 x 18 mm
- **Weight:** ≤ 50 g



 Wireless charging

PM1630 is equipped with a certified transmitter module BGM13S32A (FCC ID: QOQ13, IC: 5123A-13).
The instrument complies with the requirements of IEC 61526:2010, IEC 62743:2012 and ANSIN42.20:2006.

Integration with APDS PM530 and APDS PM531



North America

Polimaster Inc.
44873 Falcon Place, Suite 128
Sterling, VA 20166, USA
phone: +1 703 525 5075
fax: +1 703 525 5079
info@polimaster.us
www.polimaster.us

Europe

Polimaster Europe UAB
Ezero g. 4, Didziasalio k.
Nemezio sen., Vilniaus r.
LT-13264 Republic of Lithuania
phone: +370 5 210 2323
fax: +370 5 210 2324
info@polimaster.eu
www.polimaster.eu

Asia, Africa, Latin America, Australia and Oceania

Polimaster Ltd.
51, Skoriny St., Minsk
220141 Republic of Belarus
phone: +375 17 3963675, +375 17 2686819
fax: +375 17 264 2356
polimaster@polimaster.com
www.polimaster.com

Japan

Polimaster Japan Co., Ltd.
AUBE2 5-177 Kuratsuki
Kanazawa, Ishikawa Prefecture
920-8203 Japan
phone: +81 076 201 8623
fax: +81 076 201 8624
pacific@polimaster.jp
www.polimaster.jp